



**State of Georgia**  
**Department of Natural Resources**  
**Environmental Protection Division**  
**Air Protection Branch**



## Part 70 Operating Permit

**Permit Number:** 9711-051-0149-V-03-0      **Effective Date:** NOV 26 2013

**Facility Name:** Hunter Army Airfield

**Facility Address:** Savannah, Georgia 31409, Chatham County

**Mailing Address:** 1550 Veteran's Parkway  
Fort Stewart, Georgia 31314

**Parent/Holding Company:** U.S. Department of Defense, U.S. Army

**Facility AIRS Number:** 04-13-051-00149

In accordance with the provisions of the Georgia Air Quality Act, O.C.G.A. Section 12-9-1, et seq and the Georgia Rules for Air Quality Control, Chapter 391-3-1, adopted pursuant to and in effect under the Act, the Permittee described above is issued a Part 70 Permit for:

The operation of a U.S. Army Airfield providing aviation support to the 3d Infantry Division at Fort Stewart.

This Permit is conditioned upon compliance with all provisions of The Georgia Air Quality Act, O.C.G.A. Section 12-9-1, et seq, the Rules, Chapter 391-3-1, adopted and in effect under that Act, or any other condition of this Permit. Unless modified or revoked, this Permit expires five years after the effective date indicated above.

This Permit may be subject to revocation, suspension, modification or amendment by the Director for cause including evidence of noncompliance with any of the above, for any misrepresentation made in Title V Application No. TV-21398 signed on August 29, 2012, any other applications upon which this Permit is based, supporting data entered therein or attached thereto, or any subsequent submittal of supporting data, or for any alterations affecting the emissions from this source.

This Permit is further subject to and conditioned upon the terms, conditions, limitations, standards, or schedules contained in or specified on the attached 40 pages.

  
\_\_\_\_\_  
Director  
Environmental Protection Division

## Table of Contents

<b>PART 1.0</b>	<b>FACILITY DESCRIPTION .....</b>	<b>1</b>
1.1	Site Determination .....	1
1.2	Previous and/or Other Names .....	1
1.3	Overall Facility Process Description.....	1
<b>PART 2.0</b>	<b>REQUIREMENTS PERTAINING TO THE ENTIRE FACILITY .....</b>	<b>2</b>
2.1	Facility Wide Emission Caps and Operating Limits.....	2
2.2	Facility Wide Federal Rule Standards.....	2
2.3	Facility Wide SIP Rule Standards.....	2
2.4	Facility Wide Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit .....	2
<b>PART 3.0</b>	<b>REQUIREMENTS FOR EMISSION UNITS .....</b>	<b>3</b>
3.1	Emission Units .....	3
3.2	Equipment Emission Caps and Operating Limits .....	4
3.3	Equipment Federal Rule Standards.....	4
3.4	Equipment SIP Rule Standards .....	7
3.5	Equipment Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit .....	8
<b>PART 4.0</b>	<b>REQUIREMENTS FOR TESTING.....</b>	<b>9</b>
4.1	General Testing Requirements .....	9
4.2	Specific Testing Requirements .....	10
<b>PART 5.0</b>	<b>REQUIREMENTS FOR MONITORING (Related to Data Collection) .....</b>	<b>11</b>
5.1	General Monitoring Requirements.....	11
5.2	Specific Monitoring Requirements .....	11
<b>PART 6.0</b>	<b>RECORD KEEPING AND REPORTING REQUIREMENTS .....</b>	<b>14</b>
6.1	General Record Keeping and Reporting Requirements .....	14
6.2	Specific Record Keeping and Reporting Requirements.....	16
<b>PART 7.0</b>	<b>OTHER SPECIFIC REQUIREMENTS.....</b>	<b>21</b>
7.1	Operational Flexibility .....	21
7.2	Off-Permit Changes .....	21
7.3	Alternative Requirements.....	22
7.4	Insignificant Activities.....	22
7.5	Temporary Sources .....	22
7.6	Short-term Activities .....	22
7.7	Compliance Schedule/Progress Reports .....	22
7.8	Emissions Trading.....	22
7.9	Acid Rain Requirements .....	22
7.10	Prevention of Accidental Releases (Section 112(r) of the 1990 CAAA).....	22
7.11	Stratospheric Ozone Protection Requirements (Title VI of the CAAA of 1990) .....	24
7.12	Revocation of Existing Permits and Amendments.....	25
7.13	Pollution Prevention.....	25
7.14	Specific Conditions .....	25
<b>PART 8.0</b>	<b>GENERAL PROVISIONS .....</b>	<b>26</b>
8.1	Terms and References .....	26
8.2	EPA Authorities .....	26
8.3	Duty to Comply.....	26
8.4	Fee Assessment and Payment .....	27

## Title V Permit

Hunter Army Airfield

Permit No.: 9711-051-0149-V-03-0

8.5	Permit Renewal and Expiration .....	27
8.6	Transfer of Ownership or Operation .....	27
8.7	Property Rights.....	27
8.8	Submissions.....	28
8.9	Duty to Provide Information.....	28
8.10	Modifications .....	29
8.11	Permit Revision, Revocation, Reopening and Termination.....	29
8.12	Severability .....	30
8.13	Excess Emissions Due to an Emergency .....	30
8.14	Compliance Requirements .....	31
8.15	Circumvention.....	33
8.16	Permit Shield.....	34
8.17	Operational Practices .....	34
8.18	Visible Emissions.....	34
8.19	Fuel-burning Equipment .....	34
8.20	Sulfur Dioxide.....	35
8.21	Particulate Emissions .....	35
8.22	Fugitive Dust.....	36
8.23	Solvent Metal Cleaning.....	36
8.24	Incinerators.....	37
8.25	Volatile Organic Liquid Handling and Storage .....	38
8.26	Use of Any Credible Evidence or Information .....	38
8.27	Internal Combustion Engines.....	38
8.28	Boilers and Process Heaters .....	39
<b>Attachments</b>	.....	<b>40</b>
A.	List of Standard Abbreviations and List of Permit Specific Abbreviations	
B.	Insignificant Activities Checklist, Insignificant Activities Based on Emission Levels and Generic Emission Groups	
C.	List of References	

**PART 1.0 FACILITY DESCRIPTION**

**1.1 Site Determination**

There are no site determination issues regarding this facility.

**1.2 Previous and/or Other Names**

No previous names or other names have been identified.

**1.3 Overall Facility Process Description**

Hunter Army Airfield (Hunter), located in Savannah, Georgia is owned and operated by United States Army. Hunter's mission is to provide aviation support to the 3d Infantry Division (mechanized) at Fort Stewart, and includes the following activities: maneuvers training, ordnance detonation and disposal, equipment maintenance, heating and cooling services, fuel storage and fueling operations, wastewater treatment, and spray painting. There are no final products produced at Hunter Army Airfield and there are no manufacturing activities at this facility.

**PART 2.0 REQUIREMENTS PERTAINING TO THE ENTIRE FACILITY**

**2.1 Facility Wide Emission Caps and Operating Limits**

None applicable.

**2.2 Facility Wide Federal Rule Standards**

None applicable.

**2.3 Facility Wide SIP Rule Standards**

None applicable.

**2.4 Facility Wide Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit**

None applicable.

**Title V Permit**

**PART 3.0 REQUIREMENTS FOR EMISSION UNITS**

Note: Except where an applicable requirement specifically states otherwise, the averaging times of any of the Emissions Limitations or Standards included in this permit are tied to or based on the run time(s) specified for the applicable reference test method(s) or procedures required for demonstrating compliance.

**3.1 Emission Units**

Emission Units		Specific Limitations/Requirements		Air Pollution Control Devices	
ID No.	Description	Applicable Requirements/Standards	Corresponding Permit Conditions	ID No.	Description
H001	8.03 MMBtu/hr Boiler, Firing NG and No. 2 FO, Built before 1986, Building 812	391-3-1-.02(2)(d), 391-3-1-.02(2)(g),	3.2.1, 3.2.2, 3.3.2, 3.4.1, 3.4.2, 6.1.7, 6.2.2, 6.2.3, 6.2.5, 6.2.9	None	None (Stack ID = HS01)
H002	6.3 MMBtu/hr Boiler, Firing NG and No. 2 FO, Built before 1986, Building 812	391-3-1-.02(2)(d), 391-3-1-.02(2)(g),	3.2.1, 3.2.2, 3.3.2, 3.4.1, 3.4.2, 6.1.7, 6.2.2, 6.2.3, 6.2.5, 6.2.9	None	None (Stack ID = HS02)
H003	5.26 MMBtu/hr Boiler, Firing LPG and No. 2 FO, Built before 1981, Building 1031	391-3-1-.02(2)(d), 391-3-1-.02(2)(g),	3.2.1, 3.2.2, 3.3.2, 3.4.1, 3.4.2, 6.1.7, 6.2.2, 6.2.3, 6.2.5, 6.2.9	None	None (Stack ID = HS03)
H010	18.0 MMBtu/hr Boiler, Firing NG and No. 2 FO, Built in 2002, Building 1323	40 CFR 60, Subpart A, 40 CFR 60, Subpart Dc, 391-3-1-.02(2)(d), 391-3-1-.02(2)(g),	3.2.1, 3.2.2, 3.3.1, 3.3.2, 3.4.1, 3.4.2, 5.2.2, 6.1.7, 6.2.2, 6.2.3, 6.2.4, 6.2.5, 6.2.9	None	None (Stack ID = HS10)
H011	9.0 MMBtu/hr Boiler, Firing NG and No. 2 FO, Built in 2005, Ranger Barracks	391-3-1-.02(2)(d), 391-3-1-.02(2)(g),	3.2.1, 3.2.2, 3.3.2, 3.4.1, 3.4.2, 6.1.7, 6.2.2, 6.2.3, 6.2.5, 6.2.9	None	None (Stack ID = HS11)
H012	9.0 MMBtu/hr Boiler, Firing NG and No. 2 FO, Built in 2005, Ranger Barracks	391-3-1-.02(2)(d), 391-3-1-.02(2)(g),	3.2.1, 3.2.2, 3.3.2, 3.4.1, 3.4.2, 6.1.7, 6.2.2, 6.2.3, 6.2.5, 6.2.9	None	None (Stack ID = HS11)
E001	Aircraft Engine Test Cell, Design Power 1,850 Hp, Building P8045	391-3-1-.02(2)(b), 391-3-1-.02(2)(g)	3.2.1, 3.2.2, 3.4.3, 6.1.7, 6.2.2, 6.2.3, 6.2.5	None	None
E002	Aircraft Engine Test Cell, Design Power 4,777 Hp, Building P8045	391-3-1-.02(2)(b), 391-3-1-.02(2)(g)	3.2.1, 3.2.2, 3.4.3, 6.1.7, 6.2.2, 6.2.3, 6.2.5	None	None
P003	Spray Paint Booth AMCOM	391-3-1-.02(2)(b), 391-3-1-.02(2)(c)	3.4.3, 3.4.4, 3.5.1, 3.5.2, 5.2.1, 6.1.7, 6.2.1	PC03	Dry Filtration System (Stack ID = PS03)
F001-H	Corner Gasoline Dispensing Facility	40 CFR 63, Subpart CCCCCC	3.3.3, 3.3.4, 3.3.5, 3.3.6, 4.2.1, 6.2.10, 6.2.11, 6.2.12	None	None
F002-H	Kiosk Gasoline Dispensing Facility	40 CFR 63, Subpart CCCCCC	3.3.3, 3.3.4, 3.3.6, 6.2.11, 6.2.12	None	None

\* Generally applicable requirements contained in this permit may also apply to emission units listed above. The lists of applicable requirements/standards and corresponding permit conditions are intended as a compliance tool and may not be definitive.

### 3.2 Equipment Emission Caps and Operating Limits

- 3.2.1 The Permittee shall limit the total amount of fuel, including No. 2 fuel oil and Jet A, combusted in all stationary fuel burning sources at Hunter, to no more than 4,200,000 gallons during any 12 consecutive month period.  
[PSD Avoidance - 40 CFR Part 52.21]
- 3.2.2 The Permittee shall not combust distillate fuel oil or Jet A fuel in any stationary fuel burning sources at Hunter that contains greater than 0.5 weight percent sulfur. Distillate fuel oil means fuel oil that complies with the specifications for fuel oil numbers 1 or 2, as defined by the American Society for Testing and Materials in ASTM D396, "Standard Specification for Fuel Oils." Jet A fuel means fuel oil that complies with the specifications for Jet A fuel, as defined in Military Specification MIL-DTL-83133E, Turbine Fuels, Kerosene Types, NATO F-34, (Jet A), NATO F-35 and Jet A+100, Dated 1 April 1999. The fuel oil sulfur limit applies at all times, including periods of startup, shutdown, and malfunction.  
[PSD Avoidance - 40 CFR Part 52.21, 40 CFR 60.41c, and 391-3-1-.02(g) (Subsumed)]

### 3.3 Equipment Federal Rule Standards

- 3.3.1 The Permittee shall comply with all applicable provisions of the New Source Performance Standards (NSPS), 40 CFR 60, Subpart A- "General Provisions" and Subpart Dc- "Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units," for the operation of the boiler with Emission Unit ID No. H010.  
[40 CFR 60, Subpart A and Subpart Dc]
- 3.3.2 The Permittee shall comply with all applicable provisions of the National Emission Standards for Hazardous Air Pollutants (NESHAP) as found in 40 CFR 63, in Subpart A – "General Provisions," and Subpart JJJJJ – "National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boilers Area Sources."  
[40 CFR 63, Subparts A and JJJJJ]
- 3.3.3 The Permittee must not allow gasoline to be handled in a manner that would result in vapor releases to the atmosphere for extended periods of time. Measures to be taken include, but are not limited to, the following:  
[40 CFR 63.11116]
- a. Minimize gasoline spills;
  - b. Clean up spills as expeditiously as practicable;
  - c. Cover all open gasoline containers and all gasoline storage tank fill-pipes with a gasketed seal when not in use;
  - d. Minimize gasoline sent to open waste collection systems that collect and transport gasoline to reclamation and recycling devices, such as oil/water separators.

## Title V Permit

3.3.4 The Permittee shall only load gasoline into storage tanks by utilizing submerged filling. The applicable distances in paragraphs a and b shall be measured from the point in the opening of the submerged fill pipe that is the greatest distance from the bottom of the storage tank.

[40 CFR 63.11117]

- a. Submerged fill pipes installed on or before November 9, 2006, must be no more than 12 inches from the bottom of the tank.
- b. Submerged fill pipes installed after November 9, 2006, must be no more than 6 inches from the bottom of the tank.
- c. Submerged fill pipes not meeting the specifications of paragraphs a or b of this condition are allowed if the Permittee can demonstrate that the liquid level in the tank is always above the entire opening of the fill pipe.

Gasoline storage tanks with a capacity of less than 250 gallons are not required to comply with the submerged fill requirements of this condition.

3.3.5 For each gasoline dispensing facility with a monthly throughput of 100,000 gallons of gasoline or more, the Permittee must meet the requirements in either paragraph a or b of this condition. Gasoline storage tanks with a capacity of less than 250 gallons and tanks with a capacity of less than 2,000 gallons that were constructed before January 10, 2008 are exempt from this condition.

[40 CFR 63.11118]

- a. A new, reconstructed, or existing GDF Install and operate a vapor balance system on gasoline storage tanks that meets the design criteria in paragraphs i through viii.
  - i. All vapor connections and lines on the storage tank shall be equipped with closures that seal upon disconnect.
  - ii. The vapor line from the gasoline storage tank to the gasoline cargo tank shall be vapor-tight.
  - iii. The vapor balance system shall be designed such that the pressure in the tank truck does not exceed 18 inches water pressure or 5.9 inches water vacuum during product transfer.
  - iv. The vapor recovery and product adaptors, and the method of connection with the delivery elbow, shall be designed so as to prevent the over-tightening or loosening of fittings during normal delivery operations.
  - v. If a gauge well separate from the fill tube is used, it shall be provided with a submerged drop tube that extends the same distance from the bottom of the storage tank as specified in Condition 3.3.4.
  - vi. Liquid fill connections for all systems shall be equipped with vapor-tight caps.

## Title V Permit

- vii. Pressure/vacuum (PV) vent valves shall be installed on the storage tank vent pipes. The pressure specifications for PV vent valves shall be a positive pressure setting of 2.5 to 6.0 inches of water and a negative pressure setting of 6.0 to 10.0 inches of water. The total leak rate of all PV vent valves at an affected GDF, including connections, shall not exceed 0.17 cubic foot per hour at a pressure of 2.0 inches of water and 0.63 cubic foot per hour at a vacuum of 4 inches of water.
- viii. The vapor balance system shall be capable of meeting the static pressure performance requirement of the following equation:

$$Pf = 2e^{-500.887/v}$$

Where:

Pf = Minimum allowable final pressure, inches of water.

v = Total ullage affected by the test, gallons.

e = Dimensionless constant equal to approximately 2.718.

2 = The initial pressure, inches water.

For a new or reconstructed GDF, or any storage tank(s) constructed after November 9, 2006, at an existing affected facility subject to this condition, the Permittee shall equip the gasoline storage tanks with a dual-point vapor balance system.

- b. If the Permittee, prior to January 10, 2008, operates a vapor balance system at the GDF that either achieves emissions reduction of at least 90 percent or operates using management practices at least as stringent as those paragraph a of this condition, they will be deemed in compliance with this condition.
- c. Cargo tanks unloading at GDFs subject to this condition must not unload gasoline into a storage tank unless the following conditions are met:
  - i. All hoses in the vapor balance system are properly connected,
  - ii. The adapters or couplers that attach to the vapor line on the storage tank have closures that seal upon disconnect,
  - iii. All vapor return hoses, couplers, and adapters used in the gasoline delivery are vapor-tight,
  - iv. All tank truck vapor return equipment is compatible in size and forms a vapor-tight connection with the vapor balance equipment on the GDF storage tank, and
  - v. All hatches on the tank truck are closed and securely fastened.
  - vi. The filling of storage tanks at GDF shall be limited to unloading from vapor-tight gasoline cargo tanks. Documentation that the cargo tank has met the specifications of EPA Method 27 shall be carried with the cargo tank.

- 3.3.6 The Permittee must, at all times, operate and maintain each gasoline dispensing facility, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Division, which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.  
[40 CFR 63.11115]

### 3.4 Equipment SIP Rule Standards

- 3.4.1 The Permittee shall not cause, let, suffer, permit or allow the emission of fly ash and/or other particulate matter from the operation of Boilers H001, H002, H003, H010, H011 and H012, in amounts equal to or exceeding the allowable rate, calculated as follows:  
[391-3-1-.02(2)(d)]

- a. For equipment, constructed after January 1, 1972, with a rated capacity of less than 10 million BTU heat input per hour (ID Nos. H001, H002, H003, H011 and H012):  
[391-3-1-.02(2)(d)2(i)]

$$P = 0.5 \text{ pounds per million BTU heat input;}$$

- b. For equipment, constructed after January 1, 1972, with a rated capacity equal to or greater than 10 MMBtu/hr and equal to or less than 250 MMBtu/hr (ID No. H010):  
[391-3-1-.02(2)(d)2(ii)]

$$P = 0.5(10/R)^{0.5} \text{ pounds per MMBtu heat input;}$$

Where:

P = allowable weight of emissions of fly ash and/or other particulate matter in pounds per million BTU heat input

R = heat input of fuel-burning equipment in million BTU per hour

- 3.4.2 The Permittee shall not cause, let, suffer, permit or allow the emissions from Boilers H001, H002, H003, H010, H011, and H012, the opacity of which is equal to or greater than twenty (20) percent, except for one six-minute period per hour of not more than twenty-seven (27) percent opacity.  
[391-3-1-.02(2)(d)3]

- 3.4.3 The Permittee shall not discharge, or cause the discharge, into the atmosphere, from the spray paint booth with ID No. P003, and from the aircraft engine test cells with ID Nos. E001 and E002, any gases which exhibit visible emissions, the opacity of which is equal to or greater than forty (40) percent.  
[391-3-1-.02(2)(b)1.]

3.4.4 The Permittee shall not cause, let, permit, suffer, or allow the rate of emissions from the Spray Paint Booth P003, particulate matter emissions in excess of the rate derived from:  
[391-3-1-.02(2)(e)1.(i)]

a.  $E = 4.1 * P^{0.67}$ ; for process input weight rate up to and including 30 tons per hour.

b.  $E = 55 * P^{0.11} - 40$ ; for process input weight rate above 30 tons per hour.

where P equals process input weight rate in tons per hour and E equals the allowable emission rate in pounds per hour.

### 3.5 Equipment Standards Not Covered by a Federal or SIP Rule and Not Instituted as an Emission Cap or Operating Limit

3.5.1 The Permittee shall operate the dry filtration system with ID No. PC03 at all times that Spray Paint Booth P003 is in operation.  
[391-3-1-.02(2)(a)10.]

3.5.2 The Permittee shall perform dry filter changes, for the Dry Filtration System PC03, any time the light turns from green to red on the airflow monitor installed on Spray Paint Booth P003. Documentation of such filter changes shall be recorded in a log.  
[391-3-1-.02(2)(a)10.]

**PART 4.0 REQUIREMENTS FOR TESTING****4.1 General Testing Requirements**

4.1.1 The Permittee shall cause to be conducted a performance test at any specified emission unit when so directed by the Environmental Protection Division ("Division"). The test results shall be submitted to the Division within 60 days of the completion of the testing. Any tests shall be performed and conducted using methods and procedures that have been previously specified or approved by the Division.  
[391-3-1-.02(6)(b)1(i)]

4.1.2 The Permittee shall provide the Division thirty (30) days (or sixty (60) days for tests required by 40 CFR Part 63) prior written notice of the date of any performance test(s) to afford the Division the opportunity to witness and/or audit the test, and shall provide with the notification a test plan in accordance with Division guidelines.  
[391-3-1-.02(3)(a) and 40 CFR 63.7(b)(1)]

4.1.3 Performance and compliance tests shall be conducted and data reduced in accordance with applicable procedures and methods specified in the Division's Procedures for Testing and Monitoring Sources of Air Pollutants. The methods for the determination of compliance with emission limits listed under Sections 3.2, 3.3, 3.4 and 3.5 are as follows:

- a. Method 1 for the determination of sample point locations,
- b. Method 2 for the determination of stack gas flow rate,
- c. Method 3 or 3A for the determination of stack gas molecular weight,
- d. Method 4 for the determination of stack gas moisture,
- e. Method 5 for the determination of particulate matter concentration,
- f. Method 9, and the procedures contained in Section 1.3 of the above referenced document, for the determination of opacity.
- g. ASTM Test Methods D1072, D3031, D4084, or D3246 for the determination of fuel sulfur content.
- h. Method 19 when applicable, to convert particulate matter concentrations (i.e. grains/dscf), as determined using methods specified in this section, to emission rates (i.e., lb/MMBtu).

Minor changes in methodology may be specified or approved by the Director or his designee when necessitated by process variables, changes in facility design, or improvement or corrections that, in his opinion, render those methods or procedures, or portions thereof, more reliable.

[391-3-1-.02(3)(a)]

## 4.2 Specific Testing Requirements

4.2.1 For each gasoline dispensing facility with a monthly throughput of 100,000 gallons of gasoline or more, using a vapor balance system as described in Condition 3.3.5a, the Permittee must initially demonstrate compliance of the system and then must again show compliance of the vapor balance system every 3 years thereafter. The Permittee must also comply with the requirements in paragraphs a and b of this condition.  
[40 CFR 63.11120]

- a. Compliance with the leak rate and cracking pressure requirements, specified in Condition 3.3.5a.vii, for pressure-vacuum vent valves installed on gasoline storage tanks shall be demonstrated using the test methods identified in paragraph a.i or paragraph a.ii of this condition.
  - i. California Air Resources Board Vapor Recovery Test Procedure TP-201.1E,— Leak Rate and Cracking Pressure of Pressure/Vacuum Vent Valves, adopted October 8, 2003 (incorporated by reference, see § 63.14).
  - ii. Use of alternative test methods and procedures previously approved by the Division in writing.
- b. Compliance with the static pressure performance requirement specified in Condition 3.3.5a.viii of the vapor balance system shall be demonstrated by conducting a static pressure test on the gasoline storage tanks using the test methods identified in paragraphs b. i, ii, or iii of this condition.
  - i. California Air Resources Board Vapor Recovery Test Procedure TP-201.3,— Determination of 2-Inch WC Static Pressure Performance of Vapor Recovery Systems of Dispensing Facilities, adopted April 12, 1996, and amended March 17, 1999.
  - ii. Use of alternative test methods and procedures previously approved by the Division in writing.
  - iii. Bay Area Air Quality Management District Source Test Procedure ST-30— Static Pressure Integrity Test—Underground Storage Tanks, adopted November 30, 1983, and amended December 21, 1994.

If the Permittee uses a vapor balance system other than one as described in Condition 3.3.5.a, the equivalency of the that system shall be demonstrated using the procedures specified in 40 CFR 63.11120(b)(1) through (3).

**PART 5.0 REQUIREMENTS FOR MONITORING (Related to Data Collection)****5.1 General Monitoring Requirements**

- 5.1.1 Any continuous monitoring system required by the Division and installed by the Permittee shall be in continuous operation and data recorded during all periods of operation of the affected facility except for continuous monitoring system breakdowns and repairs. Monitoring system response, relating only to calibration checks and zero and span adjustments, shall be measured and recorded during such periods. Maintenance or repair shall be conducted in the most expedient manner to minimize the period during which the system is out of service.  
[391-3-1-.02(6)(b)1]

**5.2 Specific Monitoring Requirements**

- 5.2.1 The Permittee shall, for each day or portion of a day that Spray Paint Booth P003 is operated, perform an inspection of Dry Filtration System PC03. The condition of the light indicator (green or red) on the airflow monitor installed on the system shall be recorded. Any indication of improper operation of the dry filtration system and/or the need for any maintenance on the system shall be recorded in a maintenance log, along with a description of any corrective action taken and when it was completed. The filters must be changed when the light indicator goes from green to red. Filters need not be changed if P003 was not used at all in the preceding quarter. The maintenance log, including all records of filter replacement, shall be kept in a form suitable for inspection or submittal to the Division.  
[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(i)]
- 5.2.2 The Permittee shall install, calibrate, maintain, and operate monitoring devices for the measurement of the indicated parameters on the following equipment. Data shall be recorded at the frequency specified below. Where such performance specification(s) exist, each system shall meet the applicable performance specification(s) of the Division's monitoring requirements.  
[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(i) ]
- a. The quantity (cubic feet) of natural gas and distillate fuel oil (gallons) burned in Boiler H010. Data shall be recorded monthly. As an alternative, the Permittee may propose an alternative protocol for monitoring natural gas and distillate fuel oil usage. The proposal shall be submitted in writing to the Division for review and final approval.  
[40 CFR Part 60, Subpart Dc]
- 5.2.3 The Permittee shall conduct a performance tune-up on each oil-fired boiler with a heat input capacity of equal to or less than 5 million Btu per hour, including those listed in Table 5.2.3, and must thereafter conduct a tune-up of these boilers every 5 years as specified in 40 CFR 63.11223. Each 5-year tune-up must be conducted no more than 61 months after the previous tune-up. For a new or reconstructed oil-fired boiler with a heat input capacity of equal to or less than 5 million Btu per hour, the first 5-year tune-up must be no later than 61 months after the initial startup. You may delay the burner inspection specified in paragraph a of this condition and inspection of the system controlling the air-to-fuel ratio specified in

## Title V Permit

paragraph c of this condition until the next scheduled unit shutdown, but you must inspect each burner and system controlling the air-to-fuel ratio at least once every 72 months. Boilers tune-ups shall include the following:

[40 CFR 63.11223(a) and (b), Table 2 of 40 CFR 63 Subpart JJJJJJ]

- a. As applicable, inspect the burner, and clean or replace any components of the burner as necessary (you may delay the burner inspection until the next scheduled unit shutdown, but you must inspect each burner at least once every 36 months).
- b. Inspect the flame pattern, as applicable, and adjust the burner as necessary to optimize the flame pattern. The adjustment should be consistent with the manufacturer's specifications, if available.
- c. Inspect the system controlling the air-to-fuel ratio, as applicable, and ensure that it is correctly calibrated and functioning properly.
- d. Optimize total emissions of carbon monoxide. This optimization should be consistent with the manufacturer's specifications, if available.
- e. Measure the concentrations in the effluent stream of carbon monoxide in parts per million, by volume, and oxygen in volume percent, before and after the adjustments are made (measurements may be either on a dry or wet basis, as long as it is the same basis before and after the adjustments are made).
- f. Maintain onsite and submit, if requested by the Division, biennial report containing the following information:
  - i. The concentrations of CO in the effluent stream in parts per million, by volume, and oxygen in volume percent, measured before and after the tune-up of the boiler.
  - ii. A description of any corrective actions taken as a part of the tune-up of the boiler.
  - iii. The type and amount of fuel used over the 12 months prior to the biennial tune-up of the boiler.
- g. If the unit is not operating on the required date for a tune-up, the tune-up must be conducted within one week of startup.

**Title V Permit**

Hunter Army Airfield

Permit No.: 9711-051-0149-V-03-0

**Table 5.2.3**

<b>Building Number</b>	<b>Permit ID</b>	<b>Heat Input (MMBtu/hr)</b>
125	H203-H	0.414
129	H204-H	0.276
140	H203-H	0.331
145	H104-H	1.975
830	H107-H	2.000
832	H203-H	0.414
1128	H203-H	0.414
1129	H203-H	0.690
8454	H203-H	0.863
8657	Not available	2.857
8661	H145-H	1.436
8670	H203-H	0.704

**PART 6.0 RECORD KEEPING AND REPORTING REQUIREMENTS****6.1 General Record Keeping and Reporting Requirements**

6.1.1 Unless otherwise specified, all records required to be maintained by this Permit shall be recorded in a permanent form suitable for inspection and submission to the Division and to the EPA. The records shall be retained for at least five (5) years following the date of entry.

[391-3-1-.02(6)(b)1(i) and 40 CFR 70.6(a)(3)]

6.1.2 In addition to any other reporting requirements of this Permit, the Permittee shall report to the Division in writing, within seven (7) days, any deviations from applicable requirements associated with any malfunction or breakdown of process, fuel burning, or emissions control equipment for a period of four hours or more which results in excessive emissions.

The Permittee shall submit a written report that shall contain the probable cause of the deviation(s), duration of the deviation(s), and any corrective actions or preventive measures taken.

[391-3-1-.02(6)(b)1(iv), 391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(3)(iii)(B)]

6.1.3 The Permittee shall submit written reports of any failure to meet an applicable emission limitation or standard contained in this permit and/or any failure to comply with or complete a work practice standard or requirement contained in this permit which are not otherwise reported in accordance with Conditions 6.1.4 or 6.1.2. Such failures shall be determined through observation, data from any monitoring protocol, or by any other monitoring which is required by this permit. The reports shall cover each semiannual period ending June 30 and December 31 of each year, shall be postmarked by August 29 and February 28, respectively following each reporting period, and shall contain the probable cause of the failure(s), duration of the failure(s), and any corrective actions or preventive measures taken.

[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(3)(iii)(B)]

6.1.4 The Permittee shall submit a written report containing any excess emissions, exceedances, and/or excursions as described in this permit and any monitor malfunctions for each semiannual period ending June 30 and December 31 of each year. All reports shall be postmarked by August 29 and February 28, respectively following each reporting period. In the event that there have not been any excess emissions, exceedances, excursions or malfunctions during a reporting period, the report should so state. Otherwise, the contents of each report shall be as specified by the Division's Procedures for Testing and Monitoring Sources of Air Pollutants and shall contain the following:

[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(iii)(A)]

- a. A summary report of excess emissions, exceedances and excursions, and monitor downtime, in accordance with Section 1.5(c) and (d) of the above referenced document, including any failure to follow required work practice procedures.
- b. Total process operating time during each reporting period.

## Title V Permit

- c. The magnitude of all excess emissions, exceedances and excursions computed in accordance with the applicable definitions as determined by the Director, and any conversion factors used, and the date and time of the commencement and completion of each time period of occurrence.
- d. Specific identification of each period of such excess emissions, exceedances, and excursions that occur during startups, shutdowns, or malfunctions of the affected facility. Include the nature and cause of any malfunction (if known), the corrective action taken or preventive measures adopted.
- e. The date and time identifying each period during which any required monitoring system or device was inoperative (including periods of malfunction) except for zero and span checks, and the nature of the repairs, adjustments, or replacement. When the monitoring system or device has not been inoperative, repaired, or adjusted, such information shall be stated in the report.
- f. Certification by a Responsible Official that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

6.1.5 Where applicable, the Permittee shall keep the following records:  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(3)(ii)(A)]

- a. The date, place, and time of sampling or measurement;
- b. The date(s) analyses were performed;
- c. The company or entity that performed the analyses;
- d. The analytical techniques or methods used;
- e. The results of such analyses; and
- f. The operating conditions as existing at the time of sampling or measurement.

6.1.6 The Permittee shall maintain files of all required measurements, including continuous monitoring systems, monitoring devices, and performance testing measurements; all continuous monitoring system or monitoring device calibration checks; and adjustments and maintenance performed on these systems or devices. These files shall be kept in a permanent form suitable for inspection and shall be maintained for a period of at least five (5) years following the date of such measurements, reports, maintenance and records.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6 (a)(3)(ii)(B)]

6.1.7 For the purpose of reporting excess emissions, exceedances or excursions in the report required in Condition 6.1.4, the following excess emissions, exceedances, and excursions shall be reported:  
[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(iii)]

- a. Excess emissions: (means for the purpose of this Condition and Condition 6.1.4, any condition that is detected by monitoring or record keeping which is specifically defined, or stated to be, excess emissions by an applicable requirement)
- None required to be reported in accordance with Condition 6.1.4.
- b. Exceedances: (means for the purpose of this Condition and Condition 6.1.4, any condition that is detected by monitoring or record keeping that provides data in terms of an emission limitation or standard and that indicates that emissions (or opacity) do not meet the applicable emission limitation or standard consistent with the averaging period specified for averaging the results of the monitoring)
- i. Consumption of greater than 4,200,000 gallons of fuel onsite, including No. 2 fuel oil and Jet A, during any 12 consecutive month period.
  - ii. Consumption of any fuel that does not meet the specification of No. 1 or No. 2 fuel oils, or Jet A, as defined in Condition 3.2.2.
- c. Excursions: (means for the purpose of this Condition and Condition 6.1.4, any departure from an indicator range or value established for monitoring consistent with any averaging period specified for averaging the results of the monitoring)
- i. Any indication of improper operation or adverse condition of Dry Filtration System PC03, discovered during an inspection required by Condition 5.2.1.
  - ii. Any failure to operate Dry Filtration System PC03 at any time that Spray Paint Booth P003 is in operation.
  - iii. Any failure to change the filters of Dry Filtration System PC03 as required by Condition 5.2.1.
  - iv. Any failure to complete the 5 year performance tune-ups on the existing boilers in the oil subcategory, as specified in 40 CFR 63.11223.

## 6.2 Specific Record Keeping and Reporting Requirements

- 6.2.1 The Permittee shall maintain a log for Dry Filtration System PC03 at any time that Spray Paint Booth P003 is in operation. Failure to operate the air pollution control equipment as prescribed in Condition 3.5.1 shall be reported in accordance with Condition 6.1.7 and shall be indicated in the log.  
[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(i)]
- 6.2.2 The Permittee shall maintain records of all the fuel oil purchased for combustion at the base. These records shall be used to determine the 12-month rolling total consumption of fuel oil base wide. A new 12-month rolling total shall be calculated at the end of each calendar month. Records shall be available for inspection by or submission to the Division upon request.  
[391-3-1-.02(6)(b)1(ii)]

## Title V Permit

- 6.2.3 For each shipment of fuel, the Permittee shall obtain certification from the supplier that the fuel meets the fuel sulfur limits specified in Condition 3.2.2 for combustion in any stationary fuel burning source, including Boilers H001, H002, H003, H010, H011, and H012 and Aircraft Test Cell Engines E001 and E001. The certification shall contain the following:  
[391-3-1-.02(6)(b)1 and 40 CFR 70.6(a)(3)(i) and 40 CFR Part 60, Subpart Dc]
- a. For Distillate Fuel Oil
    - i. The name of the oil supplier;
    - ii. A statement from the oil supplier that the oil complies with the specifications under the definition of distillate oil in ASTM D396 for fuel oil Nos 1 or 2;
    - iii. The sulfur content or maximum sulfur content of the oil.
  - b. For Jet A Fuel:
    - i. The name of the supplier of the fuel;
    - ii. A statement from the oil supplier that the oil complies with the specifications under the definition of Jet A fuel in as contained in Military Specification MIL-DTL-83133E, Turbine Fuels, Kerosene Types, NATO F-34, (Jet A), NATO F-35 and Jet A+100, Dated 1 April 1999;
    - iii. The sulfur content or maximum sulfur content of the oil.
- 6.2.4 The Permittee shall record and maintain operational records of Boiler H010. These records shall be available for inspection or submittal to the Division upon request and contain the quantity of natural gas and distillate fuel oil combusted during each calendar month.  
[391-3-1-.02(6)(b) 1(i) and 40 CFR 60.48c(g)(2)(Subpart Dc)]
- 6.2.5 The Permittee shall submit, along with the semi-annual report required by Conditions 6.1.3 and 6.1.4, the records required by Conditions 6.2.2, 6.2.3, and 6.2.4 as a report. The report shall also include a statement signed by a responsible official of the affected base that the records of fuel supplier certifications submitted represent all of the fuel oil burned during the semi-annual period. If fuel oil was not burned during the period, the report should state that no fuel oil was burned during the semi-annual period.  
[391-3-1-.03(2)(c) and 40 CFR 60.48c(j)]
- 6.2.6 The Permittee shall submit the following notifications for each oil fired boiler subject to Subpart JJJJJ, as specified in 40 CFR 63.11225(a):  
[40 CFR 63.11225(a)]
- a. The Permittee must submit all of the notifications in 40 CFR 63.7(b); 63.8(e) and (f); 63.9(b) through (e); and 63.9(g) and (h) that apply.

## Title V Permit

- b. As specified in 40 CFR 63.9(b)(2), the Permittee must submit the Initial Notification within 120 days after a boiler becomes subject to the standard.
- c. If the Permittee is required to conduct a performance stack test, the Permittee must submit a Notification of Intent to conduct a performance test at least 60 days before the performance stack test is scheduled to begin.
- d. The Permittee must submit the Notification of Compliance Status in accordance with 40 CFR 63.9(h) within 60 days of completing the initial performance stack test. In addition to the information required in 40 CFR 63.9(h)(2), the notification must include the following certification(s) of compliance, as applicable, and signed by a responsible official:
  - i. This facility complies with the requirements in 40 CFR 63.11214 to conduct an initial tune-up of the boiler.
  - ii. This facility has had an energy assessment performed according to 40 CFR 63.11214(c), if required.
- e. If the Permittee is using data from a previously conducted emission test to serve as documentation of conformance with the emission standards and operating limits of this subpart consistent with 40 CFR 63.7(e)(2)(iv), the Permittee must submit the test data in lieu of the initial performance test results with the Notification of Compliance Status required under paragraph d.

6.2.7 The Permittee shall prepare, by March 1 of each year, and submit to the Division, an annual compliance certification report for the previous calendar year containing the information specified in 40 CFR 63.11225(b) for each boiler subject to the regulation. The Permittee must submit the report by March 15 if the Permittee had any instance described by paragraph c. For boilers that are subject only to a requirement to conduct a biennial tune-up and not subject to emission limits or operating limits, the Permittee may prepare only a biennial compliance report as specified in the paragraphs below, instead of a semi-annual compliance report. The report shall include the following:

[40 CFR 63.11225(b)]

- a. Company name and address.
- b. Statement by a responsible official, with the official's name, title, phone number, Email address, and signature, certifying the truth, accuracy and completeness of the notification and a statement of whether the source has complied with all the relevant standards and other requirements of this subpart.
- c. If the source experiences any deviations from the applicable requirements during the reporting period, include a description of deviations, the time periods during which the deviations occurred, and the corrective actions taken.
- d. The total fuel use by each affected boiler subject to an emission limit, for each calendar month within the reporting period, including, but not limited to, a

## Title V Permit

description of the fuel, whether the fuel has received a non-waste determination by the Permittee or EPA, and the total fuel usage amount with units of measure.

6.2.8 The Permittee shall maintain the following records for each oil fired boiler subject to Subpart JJJJJ, as specified in 40 CFR 63.11225(c):  
[40 CFR 63.11225(c)]

- a. As required in 40 CFR 63.10(b)(2)(xiv), the Permittee must keep a copy of each notification and report that is submitted to comply with this subpart and all documentation supporting any Initial Notification or Notification of Compliance Status that is submitted.
- b. The Permittee must keep records to document conformance with the work practices, emission reduction measures, and management practices required by 40 CFR 63.11214 as specified:
  - i. Records must identify each boiler, the date of tune-up, the procedures followed for tune-up, and the manufacturer's specifications to which the boiler was tuned.
  - ii. Records documenting the fuel type(s) used monthly by each boiler, including, but not limited to, a description of the fuel, including whether the fuel has received a non-waste determination by the Permittee or EPA, and the total fuel usage amount with units of measure.
- c. Records of the occurrence and duration of each malfunction of the boiler, or of the associated air pollution control and monitoring equipment.
- d. Records of actions taken during periods of malfunction to minimize emissions in accordance with the general duty to minimize emissions in 40 CFR 63.11205(a), including corrective actions to restore the malfunctioning boiler, air pollution control, or monitoring equipment to its normal or usual manner of operation.

6.2.9 If the Permittee intends to switch fuels, and this fuel switch may result in the applicability of a different subcategory or a switch out of subpart JJJJJ due to a switch to 100 percent natural gas, the Permittee must provide 30 days prior notice of the date upon which fuels will be switched. The notification must identify the following:  
[40 CFR 63.11225(g)]

- a. The name of the owner or operator of the affected source, the location of the source, the boiler(s) that will switch fuels, and the date of the notice.
- b. The currently applicable subcategory under this subpart.
- c. The date on which the Permittee became subject to the currently applicable standards
- d. The date upon which the Permittee will commence the fuel switch.

## Title V Permit

- 6.2.10 The Permittee shall keep records of all tests performed under Condition 4.2.1. These records shall be made available for inspection by the Division during the course of a site visit.  
[40 CFR 63.11125(a)]
- 6.2.11 The Permittee shall keep records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment at each GDF. Records of actions taken during periods of malfunction to minimize emissions, including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation shall also be maintained.  
[40 CFR 63.11125(d)]
- 6.2.12 The Permittee shall report, by March 15 of each year, the number, duration, and a brief description of each type of malfunction which occurred during the previous calendar year and which caused or may have caused any applicable emission limitation to be exceeded. The report must also include a description of actions taken by an owner or operator during a malfunction of an affected source to minimize emissions in accordance with Condition 3.3.6, including actions taken to correct a malfunction. No report is necessary for a calendar year in which no malfunctions occurred.  
[40 CFR 63.11126(b)]

**PART 7.0 OTHER SPECIFIC REQUIREMENTS****7.1 Operational Flexibility**

7.1.1 The Permittee may make Section 502(b)(10) changes as defined in 40 CFR 70.2 without requiring a Permit revision, if the changes are not modifications under any provisions of Title I of the Federal Act and the changes do not exceed the emissions allowable under the Permit (whether expressed therein as a rate of emissions or in terms of total emissions). For each such change, the Permittee shall provide the Division and the EPA with written notification as required below in advance of the proposed changes and shall obtain any Permits required under Rules 391-3-1-.03(1) and (2). The Permittee and the Division shall attach each such notice to their copy of this Permit.  
[391-3-1-.03(10)(b)5 and 40 CFR 70.4(b)(12)(i)]

- a. For each such change, the Permittee's written notification and application for a construction Permit shall be submitted well in advance of any critical date (typically at least 3 months in advance of any commencement of construction, Permit issuance date, etc.) involved in the change, but no less than seven (7) days in advance of such change and shall include a brief description of the change within the Permitted facility, the date on which the change is proposed to occur, any change in emissions, and any Permit term or condition that is no longer applicable as a result of the change.
- b. The Permit shield described in Condition 8.16.1 shall not apply to any change made pursuant to this condition.

**7.2 Off-Permit Changes**

7.2.1 The Permittee may make changes that are not addressed or prohibited by this Permit, other than those described in Condition 7.2.2 below, without a Permit revision, provided the following requirements are met:  
[391-3-1-.03(10)(b)6 and 40 CFR 70.4(b)(14)]

- a. Each such change shall meet all applicable requirements and shall not violate any existing Permit term or condition.
- b. The Permittee must provide contemporaneous written notice to the Division and to the EPA of each such change, except for changes that qualify as insignificant under Rule 391-3-1-.03(10)(g). Such written notice shall describe each such change, including the date, any change in emissions, pollutants emitted, and any applicable requirement that would apply as a result of the change.
- c. The change shall not qualify for the Permit shield in Condition 8.16.1.
- d. The Permittee shall keep a record describing changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the Permit, and the emissions resulting from those changes.

## Title V Permit

Hunter Army Airfield

Permit No.: 9711-051-0149-V-03-0

7.2.2 The Permittee shall not make, without a Permit revision, any changes that are not addressed or prohibited by this Permit, if such changes are subject to any requirements under Title IV of the Federal Act or are modifications under any provision of Title I of the Federal Act. [Rule 391-3-1-.03(10)(b)7 and 40 CFR 70.4(b)(15)]

### 7.3 Alternative Requirements

[White Paper #2]

Not Applicable

### 7.4 Insignificant Activities

(see Attachment B for the list of Insignificant Activities in existence at the facility at the time of permit issuance)

### 7.5 Temporary Sources

[391-3-1-.03(10)(d)5 and 40 CFR 70.6(e)]

Not Applicable

### 7.6 Short-term Activities

(see Form D5 "Short Term Activities" of the Permit application and White Paper #1)

Not Applicable

### 7.7 Compliance Schedule/Progress Reports

[391-3-1-.03(10)(d)3 and 40 CFR 70.6(c)(4)]

None applicable.

### 7.8 Emissions Trading

[391-3-1-.03(10)(d)1(ii) and 40 CFR 70.6(a)(10)]

Not Applicable

### 7.9 Acid Rain Requirements

Not Applicable

### 7.10 Prevention of Accidental Releases (Section 112(r) of the 1990 CAAA)

[391-3-1-.02(10)]

7.10.1 When and if the requirements of 40 CFR Part 68 become applicable, the Permittee shall comply with all applicable requirements of 40 CFR Part 68, including the following.

- a. The Permittee shall submit a Risk Management Plan (RMP) as provided in 40 CFR 68.150 through 68.185. The RMP shall include a registration that reflects all covered processes.

## Title V Permit

- b. For processes eligible for Program 1, as provided in 40 CFR 68.10, the Permittee shall comply with 7.10.1.a. and the following additional requirements:
- i. Analyze the worst-case release scenario for the process(es), as provided in 40 CFR 68.25; document that the nearest public receptor is beyond the distance to a toxic or flammable endpoint defined in 40 CFR 68.22(a); and submit in the RMP the worst-case release scenario as provided in 40 CFR 68.165.
  - ii. Complete the five-year accident history for the process as provided in 40 CFR 68.42 and submit in the RMP as provided in 40 CFR 68.168
  - iii. Ensure that response actions have been coordinated with local emergency planning and response agencies
  - iv. Include a certification in the RMP as specified in 40 CFR 68.12(b)(4)
- c. For processes subject to Program 2, as provided in 40 CFR 68.10, the Permittee shall comply with 7.10.1.a., 7.10.1.b. and the following additional requirements:
- i. Develop and implement a management system as provided in 40 CFR 68.15
  - ii. Conduct a hazard assessment as provided in 40 CFR 68.20 through 68.42
  - iii. Implement the Program 2 prevention steps provided in 40 CFR 68.48 through 68.60 or implement the Program 3 prevention steps provided in 40 CFR 68.65 through 68.87
  - iv. Develop and implement an emergency response program as provided in 40 CFR 68.90 through 68.95
  - v. Submit as part of the RMP the data on prevention program elements for Program 2 processes as provided in 40 CFR 68.170
- d. For processes subject to Program 3, as provided in 40 CFR 68.10, the Permittee shall comply with 7.10.1.a., 7.10.1.b. and the following additional requirements:
- i. Develop and implement a management system as provided in 40 CFR 68.15
  - ii. Conduct a hazard assessment as provided in 40 CFR 68.20 through 68.42
  - iii. Implement the prevention requirements of 40 CFR 68.65 through 68.87
  - iv. Develop and implement an emergency response program as provided in 40 CFR 68.90 through 68.95
  - v. Submit as part of the RMP the data on prevention program elements for Program 3 as provided in 40 CFR 68.175
- e. All reports and notification required by 40 CFR Part 68 must be submitted electronically using RMP\*eSubmit (information for establishing an account can be found at [www.epa.gov/emergencies/content/rmp/rmp\\_esubmit.htm](http://www.epa.gov/emergencies/content/rmp/rmp_esubmit.htm)). Electronic Signature Agreements should be mailed to:

MAIL

**Risk Management Program (RMP) Reporting Center  
P.O. Box 10162  
Fairfax, VA 22038**

**COURIER & FEDEX**

**Risk Management Program (RMP) Reporting Center  
CGI Federal  
12601 Fair Lakes Circle  
Fairfax, VA 22033**

Compliance with all requirements of this condition, including the registration and submission of the RMP, shall be included as part of the compliance certification submitted in accordance with Condition 8.14.1.

**7.11 Stratospheric Ozone Protection Requirements (Title VI of the CAAA of 1990)**

7.11.1 If the Permittee performs any of the activities described below or as otherwise defined in 40 CFR Part 82, the Permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for motor vehicle air conditioners (MVACs) in Subpart B:

- a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- b. Equipment used during the maintenance, service, repair, or disposal of appliance must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.
- d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with record keeping requirements pursuant to 40 CFR 82.166.  
[Note: "MVAC-like appliance" is defined in 40 CFR 82.152.]
- e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to 40 CFR 82.156.
- f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to 40 CFR 82.166.

7.11.2 If the Permittee performs a service on motor (fleet) vehicles and if this service involves an ozone-depleting substance (refrigerant) in the MVAC, the Permittee is subject to all the applicable requirements as specified in 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners.

The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term "MVAC" as used in Subpart B

## Title V Permit

Hunter Army Airfield

Permit No.: 9711-051-0149-V-03-0

does not include air-tight sealed refrigeration systems used for refrigerated cargo, or air conditioning systems on passenger buses using HCFC-22 refrigerant.

### 7.12 Revocation of Existing Permits and Amendments

The following Air Quality Permits, Amendments, and 502(b)10 are subsumed by this permit and are hereby revoked:

Air Quality Permit and Amendment Number(s)	Dates of Original Permit or Amendment Issuance
9711-051-0149-V-02-0	March 4, 2008
9711-051-0149-V-02-1	November 20, 2009

### 7.13 Pollution Prevention

None applicable.

### 7.14 Specific Conditions

None applicable.

**PART 8.0 GENERAL PROVISIONS****8.1 Terms and References**

- 8.1.1 Terms not otherwise defined in the Permit shall have the meaning assigned to such terms in the referenced regulation.
- 8.1.2 Where more than one condition in this Permit applies to an emission unit and/or the entire facility, each condition shall apply and the most stringent condition shall take precedence.  
[391-3-1-.02(2)(a)2]

**8.2 EPA Authorities**

- 8.2.1 Except as identified as "State-only enforceable" requirements in this Permit, all terms and conditions contained herein shall be enforceable by the EPA and citizens under the Clean Air Act, as amended, 42 U.S.C. 7401, et seq.  
[40 CFR 70.6(b)(1)]
- 8.2.2 Nothing in this Permit shall alter or affect the authority of the EPA to obtain information pursuant to 42 U.S.C. 7414, "Inspections, Monitoring, and Entry."  
[40 CFR 70.6(f)(3)(iv)]
- 8.2.3 Nothing in this Permit shall alter or affect the authority of the EPA to impose emergency orders pursuant to 42 U.S.C. 7603, "Emergency Powers."  
[40 CFR 70.6(f)(3)(i)]

**8.3 Duty to Comply**

- 8.3.1 The Permittee shall comply with all conditions of this operating Permit. Any Permit noncompliance constitutes a violation of the Federal Clean Air Act and the Georgia Air Quality Act and/or State rules and is grounds for enforcement action; for Permit termination, revocation and reissuance, or modification; or for denial of a Permit renewal application. Any noncompliance with a Permit condition specifically designated as enforceable only by the State constitutes a violation of the Georgia Air Quality Act and/or State rules only and is grounds for enforcement action; for Permit termination, revocation and reissuance, or modification; or for denial of a Permit renewal application.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(i)]
- 8.3.2 The Permittee shall not use as a defense in an enforcement action the contention that it would have been necessary to halt or reduce the Permitted activity in order to maintain compliance with the conditions of this Permit.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(ii)]
- 8.3.3 Nothing in this Permit shall alter or affect the liability of the Permittee for any violation of applicable requirements prior to or at the time of Permit issuance.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(f)(3)(ii)]

- 8.3.4 Issuance of this Permit does not relieve the Permittee from the responsibility of obtaining any other permits, licenses, or approvals required by the Director or any other federal, state, or local agency.  
[391-3-1-.03(10)(e)1(iv) and 40 CFR 70.7(a)(6)]

#### 8.4 Fee Assessment and Payment

- 8.4.1 The Permittee shall calculate and pay an annual Permit fee to the Division. The amount of fee shall be determined each year in accordance with the "Procedures for Calculating Air Permit Fees."  
[391-3-1-.03(9)]

#### 8.5 Permit Renewal and Expiration

- 8.5.1 This Permit shall remain in effect for five (5) years from the effective date. The Permit shall become null and void after the expiration date unless a timely and complete renewal application has been submitted to the Division at least six (6) months, but no more than eighteen (18) months prior to the expiration date of the Permit.  
[391-3-1-.03(10)(d)1(i), (e)2, and (e)3(ii) and 40 CFR 70.5(a)(1)(iii)]
- 8.5.2 Permits being renewed are subject to the same procedural requirements, including those for public participation and affected State and EPA review, that apply to initial Permit issuance.  
[391-3-1-.03(10)(e)3(i)]
- 8.5.3 Notwithstanding the provisions in 8.5.1 above, if the Division has received a timely and complete application for renewal, deemed it administratively complete, and failed to reissue the Permit for reasons other than cause, authorization to operate shall continue beyond the expiration date to the point of Permit modification, reissuance, or revocation.  
[391-3-1-.03(10)(e)3(iii)]

#### 8.6 Transfer of Ownership or Operation

- 8.6.1 This Permit is not transferable by the Permittee. Future owners and operators shall obtain a new Permit from the Director. The new Permit may be processed as an administrative amendment if no other change in this Permit is necessary, and provided that a written agreement containing a specific date for transfer of Permit responsibility coverage and liability between the current and new Permittee has been submitted to the Division at least thirty (30) days in advance of the transfer.  
[391-3-1-.03(4)]

#### 8.7 Property Rights

- 8.7.1 This Permit shall not convey property rights of any sort, or any exclusive privileges.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(iv)]

**8.8 Submissions**

- 8.8.1 Reports, test data, monitoring data, notifications, annual certifications, and requests for revision and renewal shall be submitted to:

**Georgia Department of Natural Resources  
Environmental Protection Division  
Air Protection Branch  
Atlanta Tradeport, Suite 120  
4244 International Parkway  
Atlanta, Georgia 30354-3908**

For Environmental Management District Sources, test data and requests for revisions and renewal shall be submitted to the above address. Reports, monitoring data, notifications, and annual certifications shall be copied to the above address and submitted to:

**Georgia Department of Natural Resources  
Environmental Protection Division  
Coastal District Office - Brunswick  
400 Commerce Center Drive  
Brunswick, Georgia 31523-8251**

- 8.8.2 Any records, compliance certifications, and monitoring data required by the provisions in this Permit to be submitted to the EPA shall be sent to:

**Air and EPCRA Enforcement Branch – U. S. EPA Region 4  
Sam Nunn Atlanta Federal Center  
61 Forsyth Street, SW  
Atlanta, Georgia 30303-3104**

- 8.8.3 Any application form, report, or compliance certification submitted pursuant to this Permit shall contain a certification by a responsible official of its truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

[391-3-1-.03(10)(c)2, 40 CFR 70.5(d) and 40 CFR 70.6(c)(1)]

- 8.8.4 Unless otherwise specified, all submissions under this permit shall be submitted to the Division only.

**8.9 Duty to Provide Information**

- 8.9.1 The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the Permit application, shall promptly submit such supplementary facts or corrected information to the Division.

[391-3-1-.03(10)(c)5]

## Title V Permit

- 8.9.2 The Permittee shall furnish to the Division, in writing, information that the Division may request to determine whether cause exists for modifying, revoking and reissuing, or terminating the Permit, or to determine compliance with the Permit. Upon request, the Permittee shall also furnish to the Division copies of records that the Permittee is required to keep by this Permit or, for information claimed to be confidential, the Permittee may furnish such records directly to the EPA, if necessary, along with a claim of confidentiality. [391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(v)]

### 8.10 Modifications

- 8.10.1 Prior to any source commencing a modification as defined in 391-3-1-.01(pp) that may result in air pollution and not exempted by 391-3-1-.03(6), the Permittee shall submit a Permit application to the Division. The application shall be submitted sufficiently in advance of any critical date involved to allow adequate time for review, discussion, or revision of plans, if necessary. Such application shall include, but not be limited to, information describing the precise nature of the change, modifications to any emission control system, production capacity of the plant before and after the change, and the anticipated completion date of the change. The application shall be in the form of a Georgia air quality Permit application to construct or modify (otherwise known as a SIP application) and shall be submitted on forms supplied by the Division, unless otherwise notified by the Division. [391-3-1-.03(1) through (8)]

### 8.11 Permit Revision, Revocation, Reopening and Termination

- 8.11.1 This Permit may be revised, revoked, reopened and reissued, or terminated for cause by the Director. The Permit will be reopened for cause and revised accordingly under the following circumstances: [391-3-1-.03(10)(d)1(i)]
- a. If additional applicable requirements become applicable to the source and the remaining Permit term is three (3) or more years. In this case, the reopening shall be completed no later than eighteen (18) months after promulgation of the applicable requirement. A reopening shall not be required if the effective date of the requirement is later than the date on which the Permit is due to expire, unless the original permit or any of its terms and conditions has been extended under Condition 8.5.3; [391-3-1-.03(10)(e)6(i)(I)]
  - b. If any additional applicable requirements of the Acid Rain Program become applicable to the source; [391-3-1-.03(10)(e)6(i)(II)] (Acid Rain sources only)
  - c. The Director determines that the Permit contains a material mistake or inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Permit; or [391-3-1-.03(10)(e)6(i)(III) and 40 CFR 70.7(f)(1)(iii)]

- d. The Director determines that the Permit must be revised or revoked to assure compliance with the applicable requirements.  
[391-3-1-.03(10)(e)6(i)(IV) and 40 CFR 70.7(f)(1)(iv)]
- 8.11.2 Proceedings to reopen and reissue a Permit shall follow the same procedures as applicable to initial Permit issuance and shall affect only those parts of the Permit for which cause to reopen exists. Reopenings shall be made as expeditiously as practicable.  
[391-3-1-.03(10)(e)6(ii)]
- 8.11.3 Reopenings shall not be initiated before a notice of intent to reopen is provided to the source by the Director at least thirty (30) days in advance of the date the Permit is to be reopened, except that the Director may provide a shorter time period in the case of an emergency.  
[391-3-1-.03(10)(e)6(iii)]
- 8.11.4 All Permit conditions remain in effect until such time as the Director takes final action. The filing of a request by the Permittee for any Permit revision, revocation, reissuance, or termination, or of a notification of planned changes or anticipated noncompliance, shall not stay any Permit condition.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(6)(iii)]
- 8.11.5 A Permit revision shall not be required for changes that are explicitly authorized by the conditions of this Permit.
- 8.11.6 A Permit revision shall not be required for changes that are part of an approved economic incentive, marketable Permit, emission trading, or other similar program or process for change which is specifically provided for in this Permit.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(8)]

## 8.12 Severability

- 8.12.1 Any condition or portion of this Permit which is challenged, becomes suspended or is ruled invalid as a result of any legal or other action shall not invalidate any other portion or condition of this Permit.  
[391-3-1-.03(10)(d)1(i) and 40 CFR 70.6(a)(5)]

## 8.13 Excess Emissions Due to an Emergency

- 8.13.1 An "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the Permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.  
[391-3-1-.03(10)(d)7 and 40 CFR 70.6(g)(1)]

- 8.13.2 An emergency shall constitute an affirmative defense to an action brought for noncompliance with the technology-based emission limitations if the Permittee demonstrates, through properly signed contemporaneous operating logs or other relevant evidence, that:  
[391-3-1-.03(10)(d)7 and 40 CFR 70.6(g)(2) and (3)]
- a. An emergency occurred and the Permittee can identify the cause(s) of the emergency;
  - b. The Permitted facility was at the time of the emergency being properly operated;
  - c. During the period of the emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards, or other requirements in the Permit; and
  - d. The Permittee promptly notified the Division and submitted written notice of the emergency to the Division within two (2) working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- 8.13.3 In an enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency shall have the burden of proof.  
[391-3-1-.03(10)(d)7 and 40 CFR 70.6(g)(4)]
- 8.13.4 The emergency conditions listed above are in addition to any emergency or upset provisions contained in any applicable requirement.  
[391-3-1-.03(10)(d)7 and 40 CFR 70.6(g)(5)]

## 8.14 Compliance Requirements

### 8.14.1 Compliance Certification

The Permittee shall provide written certification to the Division and to the EPA, at least annually, of compliance with the conditions of this Permit. The annual written certification shall be postmarked no later than February 28 of each year and shall be submitted to the Division and to the EPA. The certification shall include, but not be limited to, the following elements:

[391-3-1-.03(10)(d)3 and 40 CFR 70.6(c)(5)]

- a. The identification of each term or condition of the Permit that is the basis of the certification;

## Title V Permit

- b. The status of compliance with the terms and conditions of the permit for the period covered by the certification, including whether compliance during the period was continuous or intermittent, based on the method or means designated in paragraph c below. The certification shall identify each deviation and take it into account in the compliance certification. The certification shall also identify as possible exceptions to compliance any periods during which compliance is required and in which an excursion or exceedance as defined under 40 CFR Part 64 occurred;
- c. The identification of the method(s) or other means used by the owner or operator for determining the compliance status with each term and condition during the certification period;
- d. Any other information that must be included to comply with section 113(c)(2) of the Act, which prohibits knowingly making a false certification or omitting material information; and
- e. Any additional requirements specified by the Division.

### 8.14.2 Inspection and Entry

- a. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow authorized representatives of the Division to perform the following:  
[391-3-1-.03(10)(d)3 and 40 CFR 70.6(c)(2)]
  - i. Enter upon the Permittee's premises where a Part 70 source is located or an emissions-related activity is conducted, or where records must be kept under the conditions of this Permit;
  - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this Permit;
  - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this Permit; and
  - iv. Sample or monitor any substances or parameters at any location during operating hours for the purpose of assuring Permit compliance or compliance with applicable requirements as authorized by the Georgia Air Quality Act.
- b. No person shall obstruct, hamper, or interfere with any such authorized representative while in the process of carrying out his official duties. Refusal of entry or access may constitute grounds for Permit revocation and assessment of civil penalties.  
[391-3-1-.07 and 40 CFR 70.11(a)(3)(i)]

### 8.14.3 Schedule of Compliance

- a. For applicable requirements with which the Permittee is in compliance, the Permittee shall continue to comply with those requirements.  
[391-3-1-.03(10)(c)2 and 40 CFR 70.5(c)(8)(iii)(A)]

- b. For applicable requirements that become effective during the Permit term, the Permittee shall meet such requirements on a timely basis unless a more detailed schedule is expressly required by the applicable requirement.  
[391-3-1-.03(10)(c)2 and 40 CFR 70.5(c)(8)(iii)(B)]
- c. Any schedule of compliance for applicable requirements with which the source is not in compliance at the time of Permit issuance shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based.  
[391-3-1-.03(10)(c)2 and 40 CFR 70.5(c)(8)(iii)(C)]

#### 8.14.4 Excess Emissions

- a. Excess emissions resulting from startup, shutdown, or malfunction of any source which occur though ordinary diligence is employed shall be allowed provided that:  
[391-3-1-.02(2)(a)7(i)]
  - i. The best operational practices to minimize emissions are adhered to;
  - ii. All associated air pollution control equipment is operated in a manner consistent with good air pollution control practice for minimizing emissions; and
  - iii. The duration of excess emissions is minimized.
- b. Excess emissions which are caused entirely or in part by poor maintenance, poor operation, or any other equipment or process failure which may reasonably be prevented during startup, shutdown or malfunction are prohibited and are violations of Chapter 391-3-1 of the Georgia Rules for Air Quality Control.  
[391-3-1-.02(2)(a)7(ii)]
- c. The provisions of this condition and Georgia Rule 391-3-1-.02(2)(a)7 shall apply only to those sources which are not subject to any requirement under Georgia Rule 391-3-1-.02(8) – New Source Performance Standards or any requirement of 40 CFR, Part 60, as amended concerning New Source Performance Standards.  
[391-3-1-.02(2)(a)7(iii)]

#### 8.15 Circumvention

##### **State Only Enforceable Condition.**

- 8.15.1 The Permittee shall not build, erect, install, or use any article, machine, equipment or process the use of which conceals an emission which would otherwise constitute a violation of an applicable emission standard. Such concealment includes, but is not limited to, the use of gaseous diluents to achieve compliance with an opacity standard or with a standard which is based on the concentration of the pollutants in the gases discharged into the atmosphere.  
[391-3-1-.03(2)(c)]

## 8.16 Permit Shield

- 8.16.1 Compliance with the terms of this Permit shall be deemed compliance with all applicable requirements as of the date of Permit issuance provided that all applicable requirements are included and specifically identified in the Permit.  
[391-3-1-.03(10)(d)6]
- 8.16.2 Any Permit condition identified as "State only enforceable" does not have a Permit shield.

## 8.17 Operational Practices

- 8.17.1 At all times, including periods of startup, shutdown, and malfunction, the Permittee shall maintain and operate the source, including associated air pollution control equipment, in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on any information available to the Division that may include, but is not limited to, monitoring results, observations of the opacity or other characteristics of emissions, review of operating and maintenance procedures or records, and inspection or surveillance of the source.  
[391-3-1-.02(2)(a)10]

### State Only Enforceable Condition.

- 8.17.2 No person owning, leasing, or controlling, the operation of any air contaminant sources shall willfully, negligently or through failure to provide necessary equipment or facilities or to take necessary precautions, cause, permit, or allow the emission from said air contamination source or sources, of such quantities of air contaminants as will cause, or tend to cause, by themselves, or in conjunction with other air contaminants, a condition of air pollution in quantities or characteristics or of a duration which is injurious or which unreasonably interferes with the enjoyment of life or use of property in such area of the State as is affected thereby. Complying with Georgia's Rules for Air Quality Control Chapter 391-3-1 and Conditions in this Permit, shall in no way exempt a person from this provision.  
[ 391-3-1-.02(2)(a)1]

## 8.18 Visible Emissions

- 8.18.1 Except as may be provided in other provisions of this Permit, the Permittee shall not cause, let, suffer, permit or allow emissions from any air contaminant source the opacity of which is equal to or greater than forty (40) percent.  
[391-3-1-.02(2)(b)1]

## 8.19 Fuel-burning Equipment

- 8.19.1 The Permittee shall not cause, let, suffer, permit, or allow the emission of fly ash and/or other particulate matter from any fuel-burning equipment with rated heat input capacity of less than 10 million Btu per hour, in operation or under construction on or before January 1, 1972 in amounts equal to or exceeding 0.7 pounds per million BTU heat input.  
[391-3-1-.02(2)(d)]

- 8.19.2 The Permittee shall not cause, let, suffer, permit, or allow the emission of fly ash and/or other particulate matter from any fuel-burning equipment with rated heat input capacity of less than 10 million Btu per hour, constructed after January 1, 1972 in amounts equal to or exceeding 0.5 pounds per million BTU heat input.  
[391-3-1-.02(2)(d)]
- 8.19.3 The Permittee shall not cause, let, suffer, permit, or allow the emission from any fuel-burning equipment constructed or extensively modified after January 1, 1972, visible emissions the opacity of which is equal to or greater than twenty (20) percent except for one six minute period per hour of not more than twenty-seven (27) percent opacity.  
[391-3-1-.02(2)(d)]

## 8.20 Sulfur Dioxide

- 8.20.1 Except as may be specified in other provisions of this Permit, the Permittee shall not burn fuel containing more than 2.5 percent sulfur, by weight, in any fuel burning source that has a heat input capacity below 100 million Btu's per hour.  
[391-3-1-.02(2)(g)]

## 8.21 Particulate Emissions

- 8.21.1 Except as may be specified in other provisions of this Permit, the Permittee shall not cause, let, permit, suffer, or allow the rate of emission from any source, particulate matter in total quantities equal to or exceeding the allowable rates shown below. Equipment in operation, or under construction contract, on or before July 2, 1968, shall be considered existing equipment. All other equipment put in operation or extensively altered after said date is to be considered new equipment.  
[391-3-1-.02(2)(e)]

- a. The following equations shall be used to calculate the allowable rates of emission from new equipment:

$$E = 4.1P^{0.67}; \text{ for process input weight rate up to and including 30 tons per hour.}$$

$$E = 55P^{0.11} - 40; \text{ for process input weight rate above 30 tons per hour.}$$

- b. The following equation shall be used to calculate the allowable rates of emission from existing equipment:

$$E = 4.1P^{0.67}$$

In the above equations, E = emission rate in pounds per hour, and  
P = process input weight rate in tons per hour.

**8.22 Fugitive Dust**

[391-3-1-.02(2)(n)]

8.22.1 Except as may be specified in other provisions of this Permit, the Permittee shall take all reasonable precautions to prevent dust from any operation, process, handling, transportation or storage facility from becoming airborne. Reasonable precautions that could be taken to prevent dust from becoming airborne include, but are not limited to, the following:

- a. Use, where possible, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land;
- b. Application of asphalt, water, or suitable chemicals on dirt roads, materials, stockpiles, and other surfaces that can give rise to airborne dusts;
- c. Installation and use of hoods, fans, and fabric filters to enclose and vent the handling of dusty materials. Adequate containment methods can be employed during sandblasting or other similar operations;
- d. Covering, at all times when in motion, open bodied trucks transporting materials likely to give rise to airborne dusts; and
- e. The prompt removal of earth or other material from paved streets onto which earth or other material has been deposited.

8.22.2 The opacity from any fugitive dust source shall not equal or exceed 20 percent.

**8.23 Solvent Metal Cleaning**

8.23.1 Except as may be specified in other provisions of this Permit, the Permittee shall not cause, suffer, allow, or permit the operation of a cold cleaner degreaser subject to the requirements of Georgia Rule 391-3-1-.02(2)(ff) "Solvent Metal Cleaning" unless the following requirements for control of emissions of the volatile organic compounds are satisfied:

[391-3-1-.02(2)(ff)1]

- a. The degreaser shall be equipped with a cover to prevent escape of VOC during periods of non-use,
- b. The degreaser shall be equipped with a device to drain cleaned parts before removal from the unit,
- c. If the solvent volatility is 0.60 psi or greater measured at 100 °F, or if the solvent is heated above 120 °F, then one of the following control devices must be used:
  - i. The degreaser shall be equipped with a freeboard that gives a freeboard ratio of 0.7 or greater, or

- ii. The degreaser shall be equipped with a water cover (solvent must be insoluble in and heavier than water), or
- iii. The degreaser shall be equipped with a system of equivalent control, including but not limited to, a refrigerated chiller or carbon adsorption system.
- d. Any solvent spray utilized by the degreaser must be in the form of a solid, fluid stream (not a fine, atomized or shower type spray) and at a pressure which will not cause excessive splashing, and
- e. All waste solvent from the degreaser shall be stored in covered containers and shall not be disposed of by such a method as to allow excessive evaporation into the atmosphere.

## 8.24 Incinerators

- 8.24.1 Except as specified in the section dealing with conical burners, no person shall cause, let, suffer, permit, or allow the emissions of fly ash and/or other particulate matter from any incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) "Incinerators", in amounts equal to or exceeding the following:  
[391-3-1-.02(2)(c)1-4]
- a. Units with charging rates of 500 pounds per hour or less of combustible waste, including water, shall not emit fly ash and/or particulate matter in quantities exceeding 1.0 pound per hour.
  - b. Units with charging rates in excess of 500 pounds per hour of combustible waste, including water, shall not emit fly ash and/or particulate matter in excess of 0.20 pounds per 100 pounds of charge.
- 8.24.2 No person shall cause, let, suffer, permit, or allow from any incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) "Incinerators", visible emissions the opacity of which is equal to or greater than twenty (20) percent except for one six minute period per hour of not more than twenty-seven (27) percent opacity.
- 8.24.3 No person shall cause or allow particles to be emitted from an incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) "Incinerators" which are individually large enough to be visible to the unaided eye.
- 8.24.4 No person shall operate an existing incinerator subject to the requirements of Georgia Rule 391-3-1-.02(2)(c) "Incinerators" unless:
- a. It is a multiple chamber incinerator;
  - b. It is equipped with an auxiliary burner in the primary chamber for the purpose of creating a pre-ignition temperature of 800°F; and
  - c. It has a secondary burner to control smoke and/or odors and maintain a temperature of at least 1500°F in the secondary chamber.

## 8.25 Volatile Organic Liquid Handling and Storage

- 8.25.1 The Permittee shall ensure that each storage tank subject to the requirements of Georgia Rule 391-3-1-.02(2)(vv) "Volatile Organic Liquid Handling and Storage" is equipped with submerged fill pipes. For the purposes of this condition and the permit, a submerged fill pipe is defined as any fill pipe with a discharge opening which is within six inches of the tank bottom.  
[391-3-1-.02(2)(vv)(1)]

## 8.26 Use of Any Credible Evidence or Information

- 8.26.1 Notwithstanding any other provisions of any applicable rule or regulation or requirement of this permit, for the purpose of submission of compliance certifications or establishing whether or not a person has violated or is in violation of any emissions limitation or standard, nothing in this permit or any Emission Limitation or Standard to which it pertains, shall preclude the use, including the exclusive use, of any credible evidence or information, relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test or procedure had been performed.  
[391-3-1-.02(3)(a)]

## 8.27 Internal Combustion Engines

- 8.27.1 The Permittee shall comply with all applicable provisions of New Source Performance Standards (NSPS) as found in 40 CFR 60 Subpart A - "General Provisions" and 40 CFR 60 Subpart IIII - "Standard of Performance for Stationary Compression Ignition Internal Combustion Engines," for diesel-fired internal combustion engine(s) manufactured after April 1, 2006 or modified/reconstructed after July 11, 2005. Such requirements include but are not limited to:  
[40 CFR 60.4200, 391-3-1-.02(8)(b)77]
- a. Equip all emergency generator engines with non-resettable hour meters.
  - b. Purchase only diesel fuel with a maximum sulfur content of 15 ppm unless otherwise specified by the Division.
- 8.27.2 The Permittee shall comply with all applicable provisions of New Source Performance Standards (NSPS) as found in 40 CFR 60 Subpart A - "General Provisions" and 40 CFR 60 Subpart JJJJ - "Standard of Performance for Stationary Spark Ignition Internal Combustion Engines," for spark ignition internal combustion engines(s) (gasoline, natural gas, liquefied petroleum gas or propane-fired) manufactured after July 1, 2007 or modified/reconstructed after June 12, 2006.  
[40 CFR 60.4230, 391-3-1-.02(8)(b)79]
- 8.27.3 The Permittee shall comply with all applicable provisions of National Emission Standards for Hazardous Air Pollutants (NESHAP) as found in 40 CFR 63 Subpart A - "General Provisions" and 40 CFR 63 Subpart ZZZZ - "National Emission Standard for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines."  
[40 CFR 63.6580, 391-3-1-.02(9)(b)118]

**8.28 Boilers and Process Heaters**

8.28.1 The Permittee shall comply with all applicable provisions of National Emission Standards for Hazardous Air Pollutants (NESHAP) 40 CFR Part 63 Subpart A - "General Provisions" and 40 CFR 63 Subpart JJJJJ - "National Emission Standards for Hazardous Air Pollutants for Area Sources: Industrial, Commercial, and Institutional Boilers."  
[40 CFR 63.11193]

8.28.2 The Permittee shall comply with all applicable provisions of National Emission Standards for Hazardous Air Pollutants (NESHAP) 40 CFR Part 63 Subpart A - "General Provisions" and 40 CFR 63 Subpart DDDDD - "National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters."  
[40 CFR 63.7480]

**Attachments**

- A. List of Standard Abbreviations and List of Permit Specific Abbreviations
- B. Insignificant Activities Checklist, Insignificant Activities Based on Emission Levels and Generic Emission Groups
- C. List of References



**Title V Permit**

Hunter Army Airfield

Permit No.: 9711-051-0149-V-03-0

**ATTACHMENT B**

**NOTE:** Attachment B contains information regarding insignificant emission units/activities and groups of generic emission units/activities in existence at the facility at the time of Permit issuance. Future modifications or additions of insignificant emission units/activities and equipment that are part of generic emissions groups may not necessarily cause this attachment to be updated.

**INSIGNIFICANT ACTIVITIES CHECKLIST**

<b>Category</b>	<b>Description of Insignificant Activity/Unit</b>	<b>Quantity</b>
<b>Mobile Sources</b>	1. Cleaning and sweeping of streets and paved surfaces	1
<b>Combustion Equipment</b>	1. Fire fighting and similar safety equipment used to train fire fighters or other emergency personnel.	2
	2. Small incinerators that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act and are not considered a "designated facility" as specified in 40 CFR 60.32e of the Federal emissions guidelines for Hospital/Medical/Infectious Waste Incinerators, that are operating as follows:  i) Less than 8 million BTU/hr heat input, firing types 0, 1, 2, and/or 3 waste.  ii) Less than 8 million BTU/hr heat input with no more than 10% pathological (type 4) waste by weight combined with types 0, 1, 2, and/or 3 waste.  iii) Less than 4 million BTU/hr heat input firing type 4 waste. (Refer to 391-3-1-.03(10)(g)2.(ii) for descriptions of waste types)	
	3. Open burning in compliance with Georgia Rule 391-3-1-.02 (5).	1
	4. Stationary engines burning:  i) Natural gas, LPG, gasoline, dual fuel, or diesel fuel which are used exclusively as emergency generators shall not exceed 500 hours per year or 200 hours per year if subject to Georgia Rule 391-3-1-.02(2)(mmm).7  ii) Natural gas, LPG, and/or diesel fueled generators used for emergency, peaking, and/or standby power generation, where the combined peaking and standby power generation do not exceed 200 hours per year.  iii) Natural gas, LPG, and/or diesel fuel used for other purposes, provided that the output of each engine does not exceed 400 horsepower and that no individual engine operates for more than 2,000 hours per year.  iv) Gasoline used for other purposes, provided that the output of each engine does not exceed 100 horsepower and that no individual engine operates for more than 500 hours per year.	53
		7
<b>Trade Operations</b>	1. Brazing, soldering, and welding equipment, and cutting torches related to manufacturing and construction activities whose emissions of hazardous air pollutants (HAPs) fall below 1,000 pounds per year.	
<b>Maintenance, Cleaning, and Housekeeping</b>	1. Blast-cleaning equipment using a suspension of abrasive in water and any exhaust system (or collector) serving them exclusively.	
	2. Portable blast-cleaning equipment.	
	3. Non-Perchloroethylene Dry-cleaning equipment with a capacity of 100 pounds per hour or less of clothes.	
	4. Cold cleaners having an air/vapor interface of not more than 10 square feet and that do not use a halogenated solvent.	35
	5. Non-routine clean out of tanks and equipment for the purposes of worker entry or in preparation for maintenance or decommissioning.	30
	6. Devices used exclusively for cleaning metal parts or surfaces by burning off residual amounts of paint, varnish, or other foreign material, provided that such devices are equipped with afterburners.	
	7. Cleaning operations: Alkaline phosphate cleaners and associated cleaners and burners.	

## Title V Permit

Hunter Army Airfield

Permit No.: 9711-051-0149-V-03-0

### INSIGNIFICANT ACTIVITIES CHECKLIST

Category	Description of Insignificant Activity/Unit	Quantity
<b>Laboratories and Testing</b>	1. Laboratory fume hoods and vents associated with bench-scale laboratory equipment used for physical or chemical analysis.	4
	2. Research and development facilities, quality control testing facilities and/or small pilot projects, where combined daily emissions from all operations are not individually major or are support facilities not making significant contributions to the product of a collocated major manufacturing facility.	
<b>Pollution Control</b>	1. Sanitary waste water collection and treatment systems, except incineration equipment or equipment subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	1
	2. On site soil or groundwater decontamination units that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	1
	3. Bioremediation operations units that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	
	4. Landfills that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	3
<b>Industrial Operations</b>	1. Concrete block and brick plants, concrete products plants, and ready mix concrete plants producing less than 125,000 tons per year.	
	2. Any of the following processes or process equipment which are electrically heated or which fire natural gas, LPG or distillate fuel oil at a maximum total heat input rate of not more than 5 million BTU's per hour: <ul style="list-style-type: none"> <li>i) Furnaces for heat treating glass or metals, the use of which do not involve molten materials or oil-coated parts.</li> <li>ii) Porcelain enameling furnaces or porcelain enameling drying ovens.</li> <li>iii) Kilns for firing ceramic ware.</li> <li>iv) Crucible furnaces, pot furnaces, or induction melting and holding furnaces with a capacity of 1,000 pounds or less each, in which sweating or distilling is not conducted and in which fluxing is not conducted utilizing free chlorine, chloride or fluoride derivatives, or ammonium compounds.</li> <li>v) Bakery ovens and confection cookers.</li> <li>vi) Feed mill ovens.</li> <li>vii) Surface coating drying ovens</li> </ul>	
	3. Carving, cutting, routing, turning, drilling, machining, sawing, surface grinding, sanding, planing, buffing, shot blasting, shot peening, or polishing; ceramics, glass, leather, metals, plastics, rubber, concrete, paper stock or wood, also including roll grinding and ground wood pulping stone sharpening, provided that: <ul style="list-style-type: none"> <li>i) Activity is performed indoors; &amp;</li> <li>ii) No significant fugitive particulate emissions enter the environment; &amp;</li> <li>iii) No visible emissions enter the outdoor atmosphere.</li> </ul>	8
	4. Photographic process equipment by which an image is reproduced upon material sensitized to radiant energy (e.g., blueprint activity, photographic developing and microfiche).	2
	5. Grain, food, or mineral extrusion processes	
	6. Equipment used exclusively for sintering of glass or metals, but not including equipment used for sintering metal-bearing ores, metal scale, clay, fly ash, or metal compounds.	
	7. Equipment for the mining and screening of uncrushed native sand and gravel.	
	8. Ozonization process or process equipment.	
	9. Electrostatic powder coating booths with an appropriately designed and operated particulate control system.	
	10. Activities involving the application of hot melt adhesives where VOC emissions are less than 5 tons per year and HAP emissions are less than 1,000 pounds per year.	
	11. Equipment used exclusively for the mixing and blending water-based adhesives and coatings at ambient temperatures.	
	12. Equipment used for compression, molding and injection of plastics where VOC emissions are less than 5 tons per year and HAP emissions are less than 1,000 pounds per year.	
	13. Ultraviolet curing processes where VOC emissions are less than 5 tons per year and HAP emissions are less than 1,000 pounds per year.	

## Title V Permit

Hunter Army Airfield

Permit No.: 9711-051-0149-V-03-0

### INSIGNIFICANT ACTIVITIES CHECKLIST

Category	Description of Insignificant Activity/Unit	Quantity
<b>Storage Tanks and Equipment</b>	1. All petroleum liquid storage tanks storing a liquid with a true vapor pressure of equal to or less than 0.50 psia as stored.	166
	2. All petroleum liquid storage tanks with a capacity of less than 40,000 gallons storing a liquid with a true vapor pressure of equal to or less than 2.0 psia as stored that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	
	3. All petroleum liquid storage tanks with a capacity of less than 10,000 gallons storing a petroleum liquid.	3
	4. All pressurized vessels designed to operate in excess of 30 psig storing petroleum fuels that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	
	5. Gasoline storage and handling equipment at loading facilities handling less than 20,000 gallons per day or at vehicle dispensing facilities that are not subject to any standard, limitation or other requirement under Section 111 or 112 (excluding 112(r)) of the Federal Act.	14
	6. Portable drums, barrels, and totes provided that the volume of each container does not exceed 550 gallons.	100
	7. All chemical storage tanks used to store a chemical with a true vapor pressure of less than or equal to 10 millimeters of mercury (0.19 psia).	

### INSIGNIFICANT ACTIVITIES BASED ON EMISSION LEVELS

Description of Emission Units / Activities	Quantity
Fuel Dispensing of Diesel into Government Owned Vehicles, Emission Unit ID Nos. F103 and F118	2
Fuel Dispensing of Jet A into Government Owned Vehicles, Emission Unit ID Nos. F120 and F121	2
Fuel Dispensing of JP8 into Tank Trucks and at Fueling Point, Emission Unit ID Nos. F106 and F107	2
Fuel Loading of JP8 into QM Tank Trucks and into Aircraft, Emission Unit ID Nos. F122-F127	6
Fuel Loading of JP8 into Soar Tank Trucks and QM Tank Trucks, Emission Unit ID Nos. F108 and F109	2
Fuel Loading of Off-Spec Jet A into DPW Tank Trucks, Emission Unit ID Nos. F101 and F102	2
Fuel Transfer System Equipment Leaks, Building 7001 and (2) Units at Flight line, Emission Unit ID No. J101, J102, and J103	3
Spray Paint Booth, Coast Guard, Building 837, Emission Unit ID No. P102	1

ATTACHMENT B (continued)

GENERIC EMISSION GROUPS

Emission units/activities appearing in the following table are subject only to one or more of Georgia Rules 391-3-1-.02 (2) (b), (e) &/or (n). Potential emissions of particulate matter, from these sources based on TSP, are less than 25 tons per year per process line or unit in each group. Any emissions unit subject to a NESHAP, NSPS, or any specific Air Quality Permit Condition(s) are not included in this table.

Description of Emissions Units / Activities	Number of Units (if appropriate)	Applicable Rules		
		Opacity Rule (b)	PM from Mfg Process Rule (e)	Fugitive Dust Rule (n)

The following table includes groups of fuel burning equipment subject only to Georgia Rules 391-3-1-.02 (2) (b) & (d). Any emissions unit subject to a NESHAP, NSPS, or any specific Air Quality Permit Condition(s) are not included in this table.

Description of Fuel Burning Equipment	Number of Units
Fuel burning equipment with a rated heat input capacity of less than 10 million BTU/hr burning only natural gas and/or LPG.	0
Fuel burning equipment with a rated heat input capacity of less than 5 million BTU/hr, burning only distillate fuel oil, natural gas and/or LPG.	0
Any fuel burning equipment with a rated heat input capacity of 1 million BTU/hr or less.	59

## ATTACHMENT C

## LIST OF REFERENCES

1. The Georgia Rules for Air Quality Control Chapter 391-3-1. All Rules cited herein which begin with 391-3-1 are State Air Quality Rules.
2. Title 40 of the Code of Federal Regulations; specifically 40 CFR Parts 50, 51, 52, 60, 61, 63, 64, 68, 70, 72, 73, 75, 76 and 82. All rules cited with these parts are Federal Air Quality Rules.
3. *Georgia Department of Natural Resources, Environmental Protection Division, Air Protection Branch, Procedures for Testing and Monitoring Sources of Air Pollutants.*
4. *Georgia Department of Natural Resources, Environmental Protection Division, Air Protection Branch, Procedures for Calculating Air Permit Fees.*
5. Compilation of Air Pollutant Emission Factors, AP-42, Fifth Edition, Volume I: Stationary Point and Area Sources. This information may be obtained from EPA's TTN web site at [www.epa.gov/ttn/chief/ap42/index.html](http://www.epa.gov/ttn/chief/ap42/index.html).
6. The latest properly functioning version of EPA's **TANKS** emission estimation software. The software may be obtained from EPA's TTN web site at [www.epa.gov/ttn/chief/software/tanks/index.html](http://www.epa.gov/ttn/chief/software/tanks/index.html).
7. The Clean Air Act (42 U.S.C. 7401 et seq).
8. White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995 (White Paper #1).
9. White Paper Number 2 for Improved Implementation of the Part 70 Operating Permits Program, March 5, 1996 (White Paper #2).